

MAJOR DESIGN REVIEW COMPLETENESS CHECKLIST

An application for major design review is required for commercial, mixed use, industrial, institutional, and residential projects involving the issuance of a building permit for construction or reconstruction of a structure which meets any of the following criteria pursuant to Development Code Section 17.20.040.B.

- 1. New construction of residential projects with five or more dwelling units.
- 2. New single or multiple building construction, on a vacant property or parcel/lot, with an overall (or, if multiple buildings, combined) floor area of 10,001 square feet or greater.
- 3. Structural additions to an existing building where the addition has a floor area that is 50 percent or more of the floor area of the existing building or 10,001 square feet or greater, whichever is less.
- 4. New building construction, on a developed property or parcel/lot, with an overall (or, if multiple buildings, combined) floor area of 10,001 square feet or greater.
- 5. Reconstruction projects which are greater than 50 percent of the floor area of an existing building (or, if multiple buildings, 50 percent of their combined floor area) or with a floor area of 10,001 square feet or greater.
- 6. Any project being proposed on a property or a parcel/lot along, or within 500 feet, of an "Arterial Roadway" or "Boulevard" as defined by the general plan, except for structures within projects with an approved master plan.
- 7. All projects which are master planned. Once the master plan, including architectural guidelines, has been approved by the city council, individual structures may be approved by the planning director.
- 8. All shopping centers with a building with an overall (or, if multiple buildings, combined) floor area of 10,001 square feet or greater, except individual structures may be approved by the planning director where a master plan, including architectural guidelines, has been approved by the planning commission.
- 9. Certain projects within a hillside area are subject to review pursuant to chapter 17.52 (Hillside Development).
- 10. All projects subject to the requirements of chapter <u>17.138</u> (Large Site Development).



SECTION 1: Filing Requirements

| | 1. | A Major Design Review Application through our Online Permit Center at https://www.cityofrc.us/onlinepermitcenter . All concurrent applications must also be submitted prior to the subject development application being deemed complete | | | |
|---|---------|--|--|--|--|
| | 2. | A preliminary title report for all parcels included in the project no older than 60 days of the date of application. | | | |
| | 3. | Signed Property Owner Declaration Form (attached). Please upload the signed Property Owner Declaration Form to our Online Permit Center. Pursuant to California Senate Bill (SB) 1439, the Property Owner Declaration Form must be accompanied by a list which identifies all individuals and entities with financial investments or similar financial commitments to the project. | | | |
| | 4. | Signed Hazardous Waste Site Statement (attached). Please upload the signed Hazardous Waste Site Statement to ou Online Permit Center. | | | |
| | 5. | Part I of the Initial Study (Environmental Assessment). Please upload this document to our Online Permit Center. | | | |
| | 5. | Completed Climate Action Plan Consistency Review Checklist | | | |
| | | (available online at https://www.cityofrc.us/community-development/planning). Please upload this document to our Online Permit Center. | | | |
| | 6. | Development package submitted electronically (see Section 3) to be reviewed by staff for completeness and accuracy Please follow the instructions for PDF Formatting Requirements for EDR Submission (see attached PDF guidelines). | | | |
| | 7. | Water Quality Management Plan. Priority Project requirements on a separate handout are available from the Engineering Services Department. For additional information, please refer to San Bernardino County Water Quality Management Plan web site at http://permitrack.sbcounty.gov/wap/ | | | |
| | 8. | Filing Fees (see Section 2). | | | |
| | | For projects that requires supplemental noticing (see Section 17.14.050.C) Notice of Filing Signs under Public Hearing Public Notice 17.14.050. Notice of filing sign must be submitted under separate permit prior to development application deemed complete. | | | |
| SECTION 2: Filing Fees Refer to the Planning and Economic Development Department Fee List for most current fees (https://www.cityofrc.us/community-development). Additional fees may apply upon review of the application. Application fees include review for completeness review and up to 2 technical/design submittals. Additional processing fee will apply to 3 rd and subsequent technical/design submittals. Application fees include 1 st Planning Commission Hearing and/or 1 st City Council Hearing. Additional hearings may be subject to additional fees. | | | | | |
| | Major I | Design Review | | | |
| | Public | Notice (Staff Time) | | | |
| | Public | Notice (Advertising) | | | |

SECTION 3: Plan Preparation Guidelines

All plans shall be clear, legible, and accurately scaled. Please follow the instructions for PDF Formatting Requirements for EDR Submission (see attached PDF guidelines). Plans not conforming to these guidelines will not be accepted for processing.

| | 1. | All uploaded plan documents shall be provided in PDF format. In addition, the applicant is encouraged to submit CAD/3D CAD and Building Information Model (BIM) files) following the approval of a project. | | | | |
|--------|-----------|---|--|--|--|--|
| | 2. | All plans shall be drawn to an appropriate engineering and/or architectural scale, with the scale clearly labeled (Grading Plan scale should not typically exceed 1" = 40'). All elevations should, where feasible, be drawn to an architectural scale no smaller than 1/4" = 1'. All plans should be clear, legible, and accurately scaled. | | | | |
| | 3. | All plans shall be clearly labeled with the title of each sheet and have a unique sheet number. | | | | |
| | 4. | All site plans need to contain a north arrow and a legend identifying any symbols. | | | | |
| | 5. | A one-sheet index map shall be provided when a plan cannot contain the entire project on one sheet. | | | | |
| | 6. | Existing versus proposed improvements must be clearly identified and all items may not apply to all projects. | | | | |
| The it | tems list | ON 4: Contents of Development Package ted below are considered a minimum. Additional information may be necessary for clarification during the review process. At staff's ertain information contained below may not be considered required, depending on the circumstances of a particular application. | | | | |
| | A. | <u>Project Description</u> : A written project description shall accompany the application. This detailed description must include detail pertaining to the project, including but not limited to: narrative description of the project, proposed construction inclusive of proposed number of buildings, square footage to be built/added, thorough description of use, including hours of operation, number of employees, and number of parking spaces proposed. The project description shall also describe existing conditions of the site prior to proposed development. This includes a description of existing structures, uses, natural features (and whether these natural features will remain or be altered or removed). Note that additional information may be required of the project description as may be necessary depending on environmental determination. | | | | |
| | В. | <u>Site Utilization Map</u> : This map shall show the location of the site and the relationship of the proposed project to existing surrounding uses. The map shall indicate the proposed project site plan and all of the following items within a 600-foot radius: all parcel lines and streets (r.o.w., improvements, drainage facilities), location and use of structures, adjacent access and circulation, and existing zoning and land use (the scale of this map shall not be less than 1" = 100'). | | | | |
| | C. | Existing Site Plan: Where a project site or project area may be redeveloped, in part or in whole, the development package shall include an existing site plan. The existing site plan shall illustrate all existing structures and identify if these structures shall remain, be removed, or be altered. The existing site plan shall illustrate existing building sizes in square feet and a brief description of the previous use of each building. The existing site plan shall also illustrate all vehicular and pedestrian access points and all landscaping, and if these features are proposed to remain or be removed or altered. | | | | |
| | D. | Detailed Site Plan (shall include the following): | | | | |
| | | Name, address, phone number, and email address of the applicant and the author of the plan. | | | | |
| | | Property lines and lot dimensions | | | | |
| | | Site and block configurations | | | | |
| | | | | | | |



| Dimensioned locations of: | | | | | | |
|---------------------------|--|--|--|--|--|--|
| | | Setbacks (actual) from all buildings to street curb face, and the side and rear property lines. | | | | |
| | | Street dedications and improvements (existing and proposed), including overhead utilities. | | | | |
| | | Access, both vehicular and pedestrian, showing service areas and points of ingress and egress. | | | | |
| | | Off-street parking and loading or outdoor storage areas showing location, number, and typical dimension of spaces and wheel stop location (where used). | | | | |
| | | All existing street improvements and driveways on adjacent and across-the-street properties within 200 feet of the site. | | | | |
| | | All proposed public-right-of-way street improvements and street sections in compliance with City's General Plan | | | | |
| | | Any existing or planned median islands within 200 feet of the site. | | | | |
| | | All buildings within 200 feet of the site. | | | | |
| | Inter | Internal circulation pattern both vehicular and pedestrian. Show truck turning radii where applicable. | | | | |
| | Distances between buildings and/or structures. | | | | | |
| | Building and accessory structure locations, including pavement/sidewalks, trellises, light standards, trash enclosures, transformers, double detector check (DDC), Fire Department connections (FDC), and monument signs, including dimensioned setbacks (front, rear, and sides). | | | | | |
| | Location, height, and materials of walls and fences. | | | | | |
| | For residential projects: Summary Table listing each lot, its floor plan, elevation treatment, and lot coverage. Also, provide a Unit Mix Table tallying how many of each floor plan, and elevation treatment. | | | | | |
| | Total existing impervious area (square feet) | | | | | |
| | Total new impervious area (square feet) | | | | | |
| | Total removal and replacement of impervious area (square feet) Fire protection equipment (PIV, FDC, Risers, etc). | | | | | |
| E. | Conceptual Landscape Plan: This plan shall include the following: | | | | | |
| | | roposed and existing structures and improvements as shown on the detailed site plan; however, all dimensions shall keluded. Show roof outlines, including eave overhang. | | | | |
| | Cond | ceptual location of plants and a planting legend which identifies such things as: | | | | |
| | | Trees, shrubs, and ground cover areas or other softscape elements. Indicate intended function of plants (i.e. street tree, accent tree, canopy shade tree, screening hedge, etc.). | | | | |
| | | Water elements and public art. | | | | |
| | | Slope planting scheme. | | | | |



| | | Plazas, sidewalks, or other hardscape elements, such as special paving materials or rockscape. |
|---|----|--|
| | | Walls or fences and their materials. |
| | | Location and design of community amenities and a legend which identifies such things as: Common or public open space/recreation areas. |
| | | Tot lots, barbeque areas, pools/spas, recreation buildings, sports courts, etc. |
| | | Primary and secondary project entry points and their treatment (textured paving, security gates, accent planting, entry walls, and/or monument signs). |
| | | Private and public sidewalks, greenbelts, and/or equestrian trails. |
| | | Emergency vehicle access. |
| | | Line of sight (a policy handout can be requested from the Engineering Services Department) |
| | | When the project is located in a designated Rancho Cucamonga Wildland-Urban Interface Fire Area, a defensible space landscaping plan or fire protection plan is required to be approved for the project to be deemed complete. See Section 5 below. |
| 1 | F. | <u>Elevations</u> : |
| | | Illustrative elevations of all sides of all buildings and structures. "Illustrative" building elevations means drawn with shadows to give depth with people, cars, or trees for scale. Do not cover the elevation with trees, cars, or people – place them behind or on the side. For projects subject to Article VIII, clearly identify building types for each building. |
| | | Conceptual locations of commercial signage (location, size, type) with a note that all signage will be under separate permit. |
| | | Illustrative elevations of all walls and/or fences. |
| | | Illustrative cross sections and enlargements or architectural elements or details as needed. |
| | | All exterior building materials shall be clearly labeled on each sheet of elevations. |
| | | Dimension the height of the highest wall and/or roof element and the height of any architectural features such as towers or cupolas. |
| | | Front elevations for single-family residential structures shall be drawn to an architectural scale of 1/4" = 1'0" (rear and side elevations may be drawn at 1/8" = 1'0"). |
| ì | G. | Floor Plans: |
| | | All floors, including labels use of each room (bedroom, kitchen, game room, etc.) |
| | | Dimension all exterior walls, doors, windows, and room sizes. |
| 1 | Н. | Roof Plans. |



| I. | Parking Study and Parking Management Plan. For mixed-use projects pursuant to Development Code Section 17.64.060.B, a parking study prepared by a qualified traffic/parking consultant that demonstrates how proposed land uses utilize parking spaces required by Development Code Section 17.64.050. Parking study shall include a parking management plan which provides sufficient detail to satisfy requirements listed in Development Code Section 17.64.050.B.2.a-g. | | | | | | | |
|----|---|--|---|--|---|---|--|--|
| J. | | Photometric Lighting Plan. A photometric lighting plan which includes light standards and fixture detail sufficient to determine shielding and lighting requirements in compliance with Development Code Section 17.58. | | | | | | |
| K. | Phasing | Phasing Plan: If phasing is to occur, a plan shall indicate the limits of each phase. | | | | | | |
| L. | property t adjoining | Conceptual Master Plan: If the project site is located adjacent to vacant/undeveloped property and/or minimally developed property that could be subject to future additional development, then a conceptual Master Plan is required to show (on the adjoining property) potential features/improvements such as, but not limited to, building locations (commercial/industrial); subdivision layout (residential); streets; trails; parking areas; access driveways and drive aisles; and landscaping. | | | | | | |
| М. | screened | Conceptual Grading Plan: Proposed items shall be designated with solid lines and existing items with short dashes or screened. Projects which are subject to the Hillside Development Ordinance shall refer to the Ordinance for additional submittal requirements. | | | | | | |
| | open spa | Proposed grading – structures, curbs, walls (height), gutters, pavement, drainage structures, swales, mounding, slopes, open space, and trails. The plan shall include distances, spot elevations, gradients, contours, details, cross-sections, flow arrows, etc. | | | | | | |
| | Existing grading – same as for proposed grading, except shall be screened as a background for the proposed grading information. | | | | | | | |
| | IIIIOIIIIalic | on. | | | | | | |
| | | | conform to the following: | | | | | |
| | | | conform to the following: 2% or less | From 2% to 9% | Over 9% | | | |
| | | n contour intervals shall o | | From 2% to 9% 5' | Over 9% 10' | | | |
| | Maximum Prior to pr 200 feet b and floor | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of | 2% or less 2' survey, the applicant sh (label "To remain" or "To | 5' all provide a topographic map s be removed") – natural ground s (type and size), streets, trai | 10' showing the existing feat | tures, (pad | | |
| | Prior to pr 200 feet b and floor also meet | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of twith City staff to determ | 2% or less 2' survey, the applicant sh (label "To remain" or "To ourses, drainage facilitie | 5' all provide a topographic map s be removed") – natural ground s (type and size), streets, trai phy. | 10' showing the existing feat | tures, (pad | | |
| | Prior to pr 200 feet b and floor also meet Structures Cross-sec and propo | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of twith City staff to determ s – footprints, pad and flotions at all site boundaries (grading, cut versus num conditions) between | 2% or less 2' survey, the applicant sh (label "To remain" or "To ourses, drainage facilitienine the limits of topogra oor elevations, retaining ries shall be drawn to be fill conditions, wall height off-site structures and | 5' all provide a topographic map s be removed") – natural ground s (type and size), streets, trai phy. | showing the existing feat d (contours), trees, structures, and slopes. The app and vertical scale showing elevation differences xtend through building p | etures, (pad blicant may ng existing (maximum | | |
| | Prior to pr 200 feet band floor also meet Structures Cross-sec and propo and minin streets. S | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of twith City staff to determ s – footprints, pad and flotions at all site boundaries dynamics of grading, cut versus num conditions) between Sections shall be drawn in the stage of the stag | 2% or less 2' survey, the applicant sh (label "To remain" or "To ourses, drainage facilitienine the limits of topogra oor elevations, retaining ries shall be drawn to be fill conditions, wall heigh off-site structures and where the adjacent propagation of the structure of the | all provide a topographic map so be removed") – natural ground as (type and size), streets, train phy. walls and stem walls. oth an engineering horizontal asts (including retaining walls), a those on-site. Sections shall e | showing the existing feat d (contours), trees, structurely, and slopes. The apparature of the structure of t | etures, (pad blicant may ng existing (maximum bads and/or | | |
| | Prior to pr 200 feet band floor also meet Structures Cross-sec and propo and minin streets. S Separate colored in | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of twith City staff to determ a footprints, pad and flotions at all site boundaries (grading, cut versus num conditions) between Sections shall be drawn acut and fill areas with a | 2% or less 2' survey, the applicant sh (label "To remain" or "To ourses, drainage facilitienine the limits of topogra oor elevations, retaining ries shall be drawn to be fill conditions, wall heigh off-site structures and where the adjacent propaction of the clearly identified line. In plored in red. | all provide a topographic map so be removed") – natural ground as (type and size), streets, train phy. walls and stem walls. oth an engineering horizontal as the stem of the stem in the stem in the stem of th | showing the existing feat d (contours), trees, structurely, and slopes. The apparature of the structure of t | etures, (pad blicant may ng existing (maximum bads and/or | | |
| | Prior to pr 200 feet b and floor also meet Structures Cross-sec and propo and minin streets. S Separate colored in | Slope Interval reparing the topographic beyond site boundaries (elevations), drainage of twith City staff to determ a footprints, pad and flotions at all site boundaries (grading, cut versus num conditions) between Sections shall be drawn cut and fill areas with a green and cut areas couts, property lines, rights- | 2% or less 2' survey, the applicant sh (label "To remain" or "To ourses, drainage facilitienine the limits of topogra oor elevations, retaining ries shall be drawn to be fill conditions, wall heigh off-site structures and where the adjacent propaction of the clearly identified line. In plored in red. | all provide a topographic map so be removed") – natural ground as (type and size), streets, train phy. walls and stem walls. oth an engineering horizontal asts (including retaining walls), a those on-site. Sections shall everty is affected to the greatest on addition, one copy of the plant. | showing the existing feat d (contours), trees, structurely, and slopes. The apparature of the structure of t | etures, (pad blicant may ng existing (maximum bads and/or | | |



| | Retaining walls – top and footing elevations. |
|---|---|
| | Location, elevation, and size of proposed building pads. |
| | Provide a preliminary drainage report to determine storm drain requirements for the proposed development based on the drainage criteria outlined in the Engineering subdivision guidelines and drainage report requirements. Consider full development of the area bounded by the project, as well as tributary areas upstream. |
| | For new development and significant redevelopment projects where a Preliminary Project-Specific Water Quality Management Plan (WQMP) is required, the Preliminary Project-Specific WQMP may consist of only a complete WQMP Site and Drainage Plan. This Plan shall be labeled "Preliminary WQMP Site and Drainage Plan." |
| | Streets – existing and proposed cross-sections, improvements, rights-of-way, etc. Show centerline radii and gradient. |
| | Existing and proposed sewers or other method of sewering. |
| | Custom lot subdivision – show grading for streets, drainage, trails, and driveways that serve as emergency vehicle access roads (fire lanes) only. In addition, provide a separate plan showing possible future house plotting and lot grading to be completed on a lot-by-lot basis. |
| | Indicate location of benchmark(s). |
| | All sheets shall have the Geotechnical Engineer and Civil Engineer's California registration seal and original signature prior to plan submittal. |
| _ | Original plan sheets shall be sufficiently clear. Scale selected for each sheet. One inch equals 40 feet (maximum) or one inch equals 20 feet for all projects. |
| | Cut and fill quantities, exclusive of street quantities in cubic yards. These shall also be placed on the plan cover sheet in addition to submittal by letter. |
| | Detailed plans of all surface and subsurface drainage devices, walls, cribbing, dams and other protective devices to be constructed with, or as part of, the proposed work, together with a map showing the drainage area and the estimated runoff of the area served by any drains. |
| | Provide dimensions, elevations, or proposed contours to be achieved by the grading. |
| | Show side yard swale at least 3 feet away from the building with a 2 percent slope longitudinally and 5 percent minimum – 20 percent maximum transversely. |
| | Show rear yard swale at 10 feet minimum away from the building with a 2 percent minimum and 6 percent maximum slope longitudinally and 5 percent minimum – 20 percent maximum transversely, or if greater than 10 feet from the building, 1 percent minimum longitudinally. |
| | Extend the earthen swale to the back of the sidewalk when the lots are at the cul-de-sac or knuckle. |
| | Provide all wall and retaining wall height, both existing and proposed with elevations. |
| | Show typical required setbacks for corner and interior lots on the cover sheet. |
| | Show the actual setbacks (property line to structure and all distance between structures). |
| | Provide cross-sections along all the property parameters and typical interior lots. If requested, additional cross-sections shall be provided. |
| | Provide driveways with a maximum slope of 10 percent, subject to Planning review and approval. |

| | | Provide 18-foot area at 5 percent maximum slope in front of the garage. If not applicable, a driveway slope of 10 percent shall be provided. Any slopes exceeding 10 percent shall be subject to Planning and Economic Development Department review and approval. |
|------|---------|--|
| | | Total existing impervious area (square feet) |
| | | Total new impervious area (square feet) |
| | | Total removal and replacement of impervious area (square feet) |
| | N. | Overhead Utility Plan: This plan shall be drawn to scale on an 8-1/2" x 11" format showing the location and type of existing utility lines and supporting poles on both sides of all streets, alleys, railroad and flood control channel rights-of-way adjacent to the project limits and extending to the first existing pole off-site from the site boundaries (see separate handout available from the Engineering Services Department). |
| SE | CTIC | ON 5: Fire District Submittal Requirements |
| Ford | questio | ns or to obtain additional information, please contact the Fire District at RCFire@CityofRC.us or 909-477-2770 |
| | 1. | The specifics of the buildings for this project, such as use, occupancy, square footage, height, number of stories and type of construction in accordance to the current California Building code must be included in the plans. The Building and Safety Services Department and Fire District require this information to provide the applicant with a complete review and applicable comments. |
| | 2. | Annexation of the project into the Community Facilities District #85-1 or #88-1, as applicable, for fire protection services is required for new construction on sites that have not been previously annexed. Please contact the City's Special Districts division to determine if the site has been previously annexed or is required to be annexed as a condition of approval of this project. If annexation is required, proof of annexation is required for the project application to be deemed complete. |
| | 3. | Proof of available fire flow must be obtained from the water purveyor, either Cucamonga Valley Water District (CVWD) or Fontana Water Company (FWC). Allow sufficient time for the water purveyor to perform the test and produce a letter confirming the available fire flow. The applicant can submit the proof of the fire flow letter to the case file for this project through the Online Permit Center. The letter must be current (within one-year of the request) and be site specific. The fire flow requirement will be deemed complete only if the available fire flow meets or exceeds the fire flow required in accordance with the California Fire Code Chapter 9 and Appendix B. The required fire flow may be reduced by up to 75%, but not less than 1,500 GPM at 20 psi for buildings other than one- and two-family dwellings, Group R-3, R-3.1, and R-4 buildings and townhouses if the building will be equipped with an automatic fire sprinkler system in accordance with National Fire Protection Association (NFPA) Standards 13, 13R, or 13D as applicable and allowed by these standards. |
| | 4. | A fire department and emergency vehicle access plan in compliance with the minimum requirements established by Fire District Standard 5-1 is required to be submitted. The applicant is required to design the fire lanes in accordance with the Standard, including aerial apparatus access for buildings with a highest point in excess of 30 feet. If gates are proposed to be installed across emergency vehicle access roads (fire lanes) the gate locations are required to be noted and designed to the applicable Fire District Standard. |
| | 5. | A fire protection or defensible space landscape plan is required for all projects in the designated Rancho Cucamonga Wildland-Urban Interface Fire Area. For a project consisting of a single residential building of Group R-3, R-3.1, or R-4, a defensible space landscape plan in accordance with the provisions of Fire District Standard 49-1 is required to be approved for the project to be deemed complete. For all other projects, a fire protection plan in accordance with the provisions of Fire District Standard 49-1 is required to be approved for the project to be deemed complete. |
| | | a. The provisions of the Standard are applicable to new construction, additions to existing buildings and structures, the construction or placement of accessory structures on a parcel in the designated Wildland-Urban Interface Fire Area, and defensible space landscaping required by the various applicable provisions of the California Code of Regulations. |

b. When not already provided, defensible space as detailed in the Vegetation Management and Landscaping

iii. Construction or placement of a new accessory structure or an addition to an existing accessory structure.

Requirements of this Standard is required to be provided when any of the following occurs:

i. Construction of a new occupiable building or an addition to an existing occupiable building.

ii. Construction of an addition to an existing habitable or occupiable building.

iv. Approval of an outdoor storage area for a vehicle or vehicles.

Updated 05/2024



PROPERTY OWNER DECLARATION FORM

| Name of Proposed Project: | | |
|---|--|--|
| Location of Project: | | 1 |
| Assessor's Parcel Number: | | - |
| Applicant Name: | | Phone Number: Email: |
| Address: | | |
| Type of Review Requested | | |
| Certificate of Appropriateness Certificate of Economic Hardship Community Plan Amendment Minor/Conditional Use Permit Major Design Review Development Agreement Development Code Amendment Entertainment Permit General Plan Amendment Hillside Design Review Home Occupation Permit OWNER DECLARATIO I declare that, I am the owner, hereby consent to the filing of the financial commitments associated | ☐ I legally represent the owner, of real above information. Further, by signing with the proposed development have | Similar Use Determination Site Development Review Specific Plan Amendment Temporary Use Permit Tentative Subdivision Map Tree Removal Permit Uniform Sign Program Vacation of Easement Variance Zoning Map Amendment Other: property involved in this application and de, I attest that all individuals and entities with been clearly identified as required pursuan |
| Date: Signature: | attest that I can provide proof that I lega | ally represent the owner. |
| Print Name and Title: | | Phone Number: Email: |
| Address: | | |



Financial Interest Disclosure Form

Pursuant to Senate Bill 1439, please list all parties and participants as defined by Government Code Section 84308 with financial interest in the project. Provide additional sheets if necessary

| Name/Company | Name/Company |
|--------------|--------------|
| Title | |
| Name/Company | Name/Company |
| Title | Title |
| Name/Company | Name/Company |
| Title | Title |
| Name/Company | |
| Title | |



HAZARDOUS WASTE SITE STATEMENT

I have been informed by the City of Rancho Cucamonga of my responsibilities pursuant to California Government Code Section 65962.5 to notify the City as to whether the site for which a development application has been submitted is located within an area which has been designated as the location of a hazardous waste site (attached) by the Office of Planning and Research, State of California (OPR).

I have also been informed by the City of Rancho Cucamonga that, as the date of executing this statement, OPR has not yet compiled and distributed a list of hazardous waste site as required by said Section 65962.5.

I am informed and believe that the proposed site for which a development application has been submitted is not within an area specified in said Section 65962.5 as a hazardous waste site.

I declare under penalty of perjury of the laws of the State of California that the foregoing is true and correct.

| Applicant: | | |
|------------|--|--|
| | | |
| | | |
| Date: | | |

Applicants are encouraged to access the latest information related to Hazardous Waste Sites by visiting the California Department of Toxic Substance Control website at: https://dtsc.ca.gov



ONLINE PERMIT CENTER ELECTRONIC DOCUMENT REVIEW (EDR) SUBMISSION REQUIREMENTS

The City of Rancho Cucamonga Community Development Department accepts electronic plans / documents submittal via the City's *Online Permit Center* at https://www.cityofrc.us/onlinepermitcenter for permit applications.

For questions regarding the electronic submittal process, please email the Planning Department at Planning@cityofrc.us

ELECTRONIC SUBMISSION PROCESS

1. Initiate an Application

To get started, go to the City's <u>Online Permit Center</u> at https://www.cityofrc.us/onlinepermitcenter and follow the links to create an <u>Online Permit Center</u> user account. Once you have created an <u>Online Permit Center</u> user account you will then apply for the appropriate application that matches the permit you are applying for by logging into your <u>Online Permit Center</u> user account and selecting "Create an Application" (a list of record types will appear for you to select from). For all planning applications, including Design Review (DR), Conditional Use Permits (CUP), Sign Permits, Minor Design Review (MDR), etc. please select "Planning" and then "Create an Application".

Complete the application per the fields on <u>Online Permit Center</u> and follow the instructions to upload plans under "Attachments." The plans should be submitted in a <u>single black and white pdf document</u>. Plans must be scaled and oriented correctly and must not exceed 100 MB. Scanned plans will NOT be accepted. Do NOT submit individual sheets as separate multiple pdf documents. For large plan sets due to the file size, you may provide separate pdf documents for the different portions of the plans (e.g. architectural, structural, etc.), upload a separate pdf document for each supplemental document type (e.g. calculations, specifications, reports, studies, etc.). For full PDF formatting instructions, please refer to part two of this document beginning on page 2.

Once the application has been submitted, you will receive confirmation and be given a permit number. Staff will then be notified that an application has been submitted with an electronic plan submittal. Staff will then follow their internal workflow to review the plans / drawings and provide comments on the plans / drawings. If you have not been contacted within 2 business days, please email Planning@cityofrc.us.

2. Tracking Status of Your Application

All progress on your application and associated plan review can be monitored through the City's <u>Online Permit Center</u> under the "record info" tab. When City staff have completed their review of the plans / drawings electronically, you will receive an email informing you that the plans / drawings are ready with corrections or have been approved. You will need to log on to **Online Permit Center** to download the plans / drawings with all comments.

Checking your application online through the <u>Online Permit Center</u> will provide you with the latest status of your project review. You can check the <u>Online Permit Center</u> 24/7 and we recommend checking online first prior to calling City Hall.

3. Resubmittals

If resubmittals are required, there will be a link located in the "Attachment" section labeled "Resubmit" for you to upload your new plans to the open record in the <u>Online Permit Center</u>. A complete set of any plans/ drawings that were revised must

Updated 2/2020 Page 1 of 4



be uploaded, with all revisions clearly marked. Scanned plans will **NOT** be accepted. Do **NOT** submit individual plan sheets as separate PDF documents. If any resubmittal fees are due, as identified in the plan review comments or noted as a fees due online, then these must be paid at the time of resubmittal and may be paid by credit card online through the **Online Permit Center**.

4. Approval

Once all review activities are completed and the project has been approved, the City-stamped permit set of plans / drawings will be available on *Online Permit Center*.

Applicants are responsible for printing a City-stamped set of plans for use in the field by contractors and inspectors.

PDF FORMATTING REQUIREMENTS

Portable Document Format (PDF) is the industry standard for electronic plans. The City of Rancho Cucamonga only accepts PDF files for plan review. PDF files must be properly formatted as described below. <u>Please read the following instructions carefully</u>. Improperly formatted plans can delay the plan review process for your project.

Layers: No multiple layers. Layers must be merged or flattened.

Format: Vector preferred

Resolution: 300 pixels per inch (PPI)


Color Depth: Monochrome (1-bit)

File Size: 1 megabyte (MB) avg. per sheet.

100 MB total

Grouping: Multiple-sheet PDF (single file with

multiple sheets)




plans.pdf (multiple sheets)

✓ Correct


See "Formatting Q&A" on page 4 for more information on PDF file formatting and tips on how to create, convert, and merge PDF files. Each sheet of the plans must be sealed and signed by the designer of record. The signature may be applied to the drawing electronically (CCR Title 16, Div. 5, Sec. 411e).

Updated 2/2020 Page 2 of 4





All sheets must be consolidated into one plan set up to a maximum size of 100 MB whenever possible. Please consolidate plans to the fewest number of files possible.



Incorrect sheet size, scale, or margins will not be accepted.



Color plans will not be accepted.



Incorrect orientation will not be accepted

FORMATTING Q&A:

Question: Why does Rancho Cucamonga only accept PDF plans?

Updated 2/2020 Page 3 of 4



Answer:

Rancho Cucamonga is responsible for maintaining records of plans and providing the public with access to them. Files kept in our electronic database must be compatible with a wide range of computer software for storage, viewing, and printing. In addition, the file sizes must be manageable for transfer and for use by the public and City staff.

The PDF standard is constantly evolving and Rancho Cucamonga will continue to evaluate these standards as necessary.

Question:

Are raster-based PDF files acceptable?

Answer:

Yes, assuming they meet the size limitation requirement of no more than 100 MB total. Vector-based PDF files are typically much larger than raster-based files. However, the City prefers vector-based files given the ability to scale these files.

Question:

How do I combine multiple PDFs into a single file?

Answer:

There are numerous PDF tools freely available on the Internet, which can be used to merge, rotate, and rearrange PDF files.

Question:

My PDF files are too big. What am I doing wrong?

Answer:

Properly formatted and compressed raster PDF files should not exceed 1MB per sheet. If your files are larger, you may have made one of the following errors:

- Saving the plans as 8-bit (grayscale) or 24-bit (full-color) raster files will drastically increase the file size. Even if the images contain only black and white objects, 8-bit and 24-bit files still contain all of the shade and color data. Plans must be saved as 1-bit (monochrome).
- Uncompressed files are much larger than compressed files. Construction plans contain mostly
 white space. The data required to store this white space can be significantly reduced. When
 converting your PDFs to raster images, be sure to use a form of lossless compression (such as
 LZW). When creating or saving PDF files, remember to specify "compressed."

Question:

How do I convert a vector-based PDF to a raster-based PDF if my file size is too large?

Answer:

The industry standard software for working with PDF files is Adobe Acrobat; however, there are numerous PDF tools freely available on the Internet.

- Step 1: Save the vector-based PDF files as raster images (TIF or PNG). The format of the raster images is important (300 ppi, monochrome). We recommend TIF files with LZW compression.
- Step 2: Convert the raster images back to compressed PDF files.
- Step 3: Merge the individual PDF files into a single multi-sheet PDF file.

Question:

Some raster images are loading slowly in the PDF reader. What am I doing wrong?

Answer:

Transparent raster images require considerable resources to display. Even though the source image is not transparent, your CAD software may be plotting it with transparency (white pixels plotted as see-thru). Be sure to set image transparency "off" before plotting.

Updated 2/2020 Page 4 of 4